

## Attaching and removing your Massey Ferguson backhoe is easy as 1-2-3.



**Step 1**  
Lower stabilizers slightly off the ground. Extend boom to raise tractor slightly and remove mounting pins.



**Step 2**  
Use boom to let backhoe roll back and out of the cradle.



**Step 3**  
Lower stabilizers to steady backhoe while storing. Shut off tractor and disconnect hydraulic hoses.

BACKHOE MODEL	CB15	CB20	CB25
Dipper digging force: lbs. (kg)	1,900 (862)	2,600 (1,179)	2,496 (1,132)
Bucket digging force: lbs. (kg)	3,250 (1,474)	4,160 (1,887)	3,160 (1,433)
Maximum digging depth: in. (mm)	90 (2,286)	100 (2,540)	123.5 (3,137)
Maximum reach: in. (mm)	112 (2,845)	127 (3,226)	162 (4,115)
Swing arc: degrees	180	180	180
Standard-duty bucket options: in.	10, 12, 16, 24 & 37	10, 12, 16, 24 & 37	N/A
Standard-duty bucket options: mm	254, 305, 406, 610 & 940	254, 305, 406, 610 & 940	N/A
Heavy-duty bucket options: in.	12, 16 & 24	12, 16 & 24	12, 16, 24 & 37
Heavy-duty bucket options: mm	305, 406 & 610	305, 406 & 610	305, 406, 610 & 940
Compatible tractor models	1635, 1643, 1648, 1652, 1655	1635, 1643, 1648, 1652, 1656	1660